



PRODUCT DATA

PD 105

AQUARIGHT PP 205

**DESCRIPTION
AND USE**

AQUARIGHT PP 205 is a blend of phosphate based combine with polymers for internal boiler water treatment. The formulation designed to control the problems of scale and deposits in Hot water or steam boilers.

AQUARIGHT PP 205 can be used to provide phosphate treatment control scale consistent with British Standard 2486 : 1997

**GENERAL
SPECIFICATION**

Appearance : Yellowish
Specific gravity : 1.17
pH : 11.5
Solubility : miscible with water

**TREATMENT
AND DOSAGE
REQUIREMENTS**

AQUARIGHT PP 205 is normally dosed to the boiler feed line either diluted or a stock concentrate solution. Dosage will vary depending on the operating characteristics of individual boiler system and the feed water condition. The optimum dosage will be recommended by your AQUARIGHT representative or agent to ensure reliable performance.

**PRODUCT
BENEFITS**

Established form of treatment consistent with British Standard 2486 : 1997

Contain organic polymer will be helps maintain particulate matter in suspension enable it to be discharged in the boiler blowdown.

Can helps breakdown existing deposits in the boiler.

Easily monitored by analysis.

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia