

PRODUCT DATA

AQUARIGHT KP 35 AC

DESCRIPTION AND USE **AQUARIGHT KP 35 AC** is an inorganic, Polyaluminium chloride based solution. Differently from other organic flocculants, the **AQUARIGHT KP 35 AC** when over dosage, does not produce an increase in treated water turbidity and this feature make it particularly suitable for the flocculation those waters turbidity could largely by rapidly change.

GENERAL SPESIFICATION

Appearance	: Yellowish
pH	: 2.0 – 4.0
Spesific gravity	: 1.20 – 1.25
Solubility	: Soluble in water

TRAE TMENT AND DOSAGE REQUIREMENTS **AQUARIGHT KP 35 AC** in general dosage range at 5 to 10 ppm slightly different dosage could be necessary depending upon water characteristics.
The correct dosage must be established by field test (Jartest)

PRODUCT BENEFITS The activity of the product cover a wide ph range.

Very effective both in primary and waste water treatment, in flotation process and for sludge de-watering.

Supplied in liquid form, easy and ready to use.

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia