



PRODUCT DATA

PD 107

AQUARIGHT MK 01

DESCRIPTION AND USE

AQUARIGHT MK 01 is a neutralizing amine, based on cyclohexylamine, used to correct the pH of condensate and to prevent corrosion in steam lines. In hot water circuits, where the make-up is of de-mineralized water quality.

AQUARIGHT MK 01 may be employed to obtain the required pH, and prevent corrosion.

GENERAL SPECIFICATION

Appearance : Clear
Specific Gravity : 0.95
pH : 12

TREATMENT AND DOSAGE REQUIREMENTS

For steam boilers, the rate of dosing is dependent on the CO₂ present in the steam, and it will be established by PT ZEFA VALINDO JAYA to suit the particular circumstances.

AQUARIGHT MK 01 should be dilute as required, with clean water, and injected continuously by a dosage pump. For hot water circuits, the AQUARIGHT MK 01 dose should normally be adjusted to maintain the circuit above pH 8.5, but optimum pH levels will be specified by PT ZEFA VALINDO JAYA.

AQUARIGHT MK 01 may be injected without dilution.

PRODUCT BENEFITS

Controls condensate pH

Prevents corrosion due to dissolved CO₂

Liquid product, for ease of use

Simple control tests

May be used in low solids programmes

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia