



**PRODUCT DATA**

PD 135

# AQUARIGHT FC 703

**DESCRIPTION  
AND USE**

AQUARIGHT FC - 703 is a liquid non ionic polymer designed to aid filtration system. It is use in potable water and industrial influent an effluent treatment.

AQUARIGHT FC - 703 can be used in all water types, including sea water and brackish water foe use in reverse Osmosis plant. It is fully compatible with all types of membrane system

**GENERAL  
SPECIFICATION**

Appearance : Pale Yellow Liquid  
pH : 6.5  
Specific gravity : 1.02  
Viscosity (cps)<sup>3</sup> : 150

**TREATMENT  
AND DOSAGE  
REQUIREMENTS**

AQUARIGHT FC - 703 should be dosed as a dilute solution of 10 % or less. The optimum dosage rates depends upon the feed water conditions, and will typically vary from 0.5 to 3.0 ppm.

AQUARIGHT FC – 703 should be added as early in the system as practicable and always before filtration system.

**PRODUCT  
BENEFITS**

Fast settling rates

Work over wide pH range

Liquid product, safe and easy to handle

Enhances the performance of all types of filtration equipment

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia